



# MSDS

## MATERIAL SAFETY DATA SHEET

PRODUCT TRADE NAME:

HOMAX PRODUCTS, INC.  
**NAIL HOLE PATCH  
FOR WALLS & CEILINGS**  
ITEM #5520, 710814

HAZARDOUS MATERIAL INFORMATION SYSTEM	
HEALTH	2
FLAMMABILITY	0
REACTIVITY	0
PROTECTIVE EQUIPMENT	A

(HAZARD RATING: 0=LEAST, 1=SLIGHT, 2=MODERATE, 3=HIGH, 4=EXTREME) (A=SAFETY GLASSES)

### SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME:  
HOMAX PRODUCTS, INC.  
468 W. HORTON RD.  
BELLINGHAM WA 98226

24 HOUR EMERGENCY PHONE NUMBER:  
CHEMTREC 1-800-424-9300  
INFORMATION PHONE NUMBER: 1-800-729-9029  
DATE OF PREPARATION: 01/15/03

### SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

CAS NUMBER	DESCRIPTION	PEL	TLV	%
1317653	CALCIUM CARBONATE	15mg/m3		
1332587	KAOLIN CLAY			
57556	PROPYLENE GLYCOL	1mgm/m3		
25067021	VINYL ACRYLIC COPOLYMER			
7732185	WATER			

### SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

APPEARANCE AND ODOR: GRAYISH-WHITE LIQUID WITH TYPICAL LATEX ODOR.

BOILING RANGE: >212F

EVAPORATION RATE: SLOWER THAN ETHER

VAPOR PRESSURE: NA  
WATER SOLUBILITY (%): 100  
VAPOR DENSITY (AIR = 1): NA  
WEIGHT PER GALLON 15LBS.

SPECIFIC GRAVITY (WATER = 1)  
% VOLATILITY BY VOLUME:  
% VOLATILITY BY WEIGHT:

NA  
NA

N/E – NOT ESTABLISHED

---

**SECTION IV – FIRE AND EXPLOSION DATA**

---

FLASH POINT & METHOD: N/A  
FLAMMABLE LIMITS:  
LEL:  
UEL:  
EXTINGUISHING MEDIA: N/A  
SPECIAL FIRE FIGHTING  
PROCEDURES:  
UNUSUAL FIRE AND EXPLOSION NO HAZARD  
HAZARDS:  
DOT NON-FLAMMABLE

---

**SECTION V – REACTIVITY DATA**

---

STABILITY:

STABLE

HAZARDOUS POLYMERIZATION  
WILL NOT OCCUR

---

**SECTION VI – HEALTH HAZARD DATA**

---

ROUTES OF ENTRY: INHALATION – YES SKIN – YES

HEALTH HAZARDS :

SUBCHRONIC (TARGET ORGAN EFFECTS)

INHALATION:

ACUTE OVEREXPOSURE IN MIST FORM MAY RESULT IN IRRITATION OF THROAT AND LUNGS

INGESTION:

SEVERE ORAL INTOXICATION WILL LEAD TO INTENSE BURNING OF THE THROAT AND MAY RESULT IN DROWSINESS, NUMBNESS, AND HEADACHE FOLLOWED BY WEAKNESS AND NAUSEA.

CARCINOGENICITY:

NTP: NO IARC MONOGRAPHS: NO OSHA REGULATED: NO

EMERGENCY AND FIRST AID PROCEDURES:

IF INHALED:

REMOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION.

EYE CONTACT:

FLUSH WITH WATER. SEEK MEDICAL ATTENTION.

SKIN CONTACT:

IMMEDIATELY WASH SKIN WITH LOTS OF SOAP AND WATER.

INGESTION:

DO NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION.

---

**SECTION VII – PRECAUTIONS FOR SAFE HANDLING AND USE**

---

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

COLLECT LARGE SPILLS WITH SHOVEL OR PUMP. SPREAD SAND OVER SPILL AREAS. CLEAN WITH DETERGENT SOLUTION. REMOVE ALL IGNITION SOURCES. ABSORB WITH ABSORBENT. SWEEP OR SCOOP UP VENTILATE.

**WASTE DISPOSAL METHOD:**

DISPOSE WASTE BY SANITARY LANDFILL OR INCINERATION IN ACCORDANCE WITH APPROPRIATE REGULATIONS.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:**

KEEP AWAY FROM HEAT AND OPEN FLAMES. KEEP FROM FREEZING. USE WITH ADEQUATE VENTILATION.

---

**SECTION VIII – CONTROL MEASURES**

---

**RESPIRATORY PROTECTION:**

USE MASK WHILE SPRAYING. AVOID INHALATION.

**VENTILATION:**

SUFFICIENT VENTILATION TO KEEP WITHIN OSHA PEL/TLV LIMIT. THE DRIED FILM OF THIS PRODUCT MAY CONTAIN ALL OR SOME OF THE FOLLOWING OSHA CHEMICALS AND MAY BECOME A DUST NUISANCE WHEN REMOVED BY SANDING OR GRINDING. OSHA RECOMMENDS A PEL/TWA OF 15MG/M3 FOR THE RESPIRABLE FRACTION. ACGIH RECOMMENDS TLV/TWA OF 10 MG/M3 FOR TOTAL DUST. USE APPROVED MASK AND EYE AND GLOVES WHILE GRINDING. SKIN ABSORPTION MAY CONTRIBUTE TO THE OVERALL EXPOSURE TO THIS MATERIAL.

**SKIN:**

USE PROTECTIVE GLOVES.

**EYE PROTECTION:**

WEAR GOGGLES TO AVOID SPLASH.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:**

LONG-SLEEVED SHIRT, TROUSERS AND SAFETY SHOES.

---

**SECTION IX - DISCLAIMER**

---

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE, OBTAINED FROM SOURCES BELIEVED BY HOMAX PRODUCTS, INC. TO BE ACCURATE. SINCE THE CONDITIONS AND METHODS OF USE OF OUR PRODUCTS ARE BEYOND OUR CONTROL, WE DISCLAIM ANY AND ALL LIABILITY ARISING OUT OF THE IMPROPER USE OF THESE PRODUCTS OR THE INFORMATION PROVIDED HEREWITH.